

MERZ clever&smart Room Sensor Clima WiFi 3 F810 44

Digital room temperature and humidity sensor with communication via WiFi module 2.4 GHz in connection with the HERZ clever&smart Control Box Clima.




Power Supply power consumption Measurement Range

Technical Data

	Accuracy +/- 1 °C / +/- 6 % Resolution 0.1 °C / 0.1 %
Protection Class	IP 20
Dimension	55 mm x 55 mm
Housing Design	plastic housing pure white
Installation Methods	Surface / flush-mounted

💟 Wall Installation



Mount the HERZ clever&smart Room Sensor Clima WiFi in a suitable place.

230 VAC

1 W - 2,5 W

0 °C ... 60 °C / 0 % ... 100 %



Caution! Device and function may be damaged. Select a suitable environmental condition. Direct sunlight, sources of heat and cold, e.g. radiators and windows must be avoided.

Mounting in flush-mounted switch box

Attach the mounting ring to the switch box. Open the terminals with a screwdriver and make the electrical connection as described below.

Electrical connection

Connect the sensor to the 230 VAC power supply as shown (blue = neutral conductor N, brown = outer conductor L).

Attach insert

Neutral conductor N

Outer conductor L

Hold the cover frame (1 - not included in the scope of delivery) against the mounting ring (2). Align the HERZ clever&smart Room Sensor Clima WiFi (3) to fit the mounting ring and push it on.

Surface-mounted

Use the surface-mounted frame high set 3 F810 53 for surface-mounted installation.

Pairing HERZ clever&smart Room Controller with HERZ clever&smart Room Sensor Clima WiFi



Expert > Settings > Devices







Confirm integration




HERZ clever&smart Room Sensor Clima WiFi room assignment

There are two ways to assign a room to the HERZ clever&smart Room Sensor Clima WiFi:

1. Using the unit ID via the HERZ clever&smart Room Controller menu 'Expert -> Settings -> Room X -> Temperature / Humidity'.

2. As described under 1. via the HERZ clever&smart Room Controller menu in combination with the Touch-To-Assign function (T2A) on the HERZ clever&smart Room Sensor Clima WiFi.



☑ Load factory settings

To unpair a HERZ clever&smart Room Sensor Clima WiFi with a HERZ clever&smart Room Controller WiFi or to reset the HERZ clever&smart Room Sensor Clima WiFi to factory settings:

- 1. Briefly tap the top right of the touch area twice with your finger.
- 2. Place your finger on the top right of the touch area for a long time. After 5 seconds, the LEDs flash red. Continue to hold until the LEDs go out.
- 3. Then at the HERZ clever&smart Room Controller WiFi in the menu:

Expert > Settings > Devices > WiFi Sensor > Remove to exclude the sensor.

