

# HERZ-Distributor Cabinet

Standard Sheet for  
8569  
Edition 0424

- Depth adjustable from 80–110 mm
- Cabinet height adjustable from 705–775 mm
- Front plate can be removed, adjustable from 80–100 mm, with integrated plug-in door with sash lock, 546 mm high
- Height-adjustable legs
- Adjustable fastening bars for distributor holding device
- Frame and cabinet walls of hot galvanised sheet steel
- Front door and front frame with a white enamel coat (RAL 9016)
- Protective plate for preventing entry of material during preparation of the wash floor is removable and adjustable, 110 mm high
- Pipe deflection rail can be removed for convenient installation of soft steel and plastic pipes.
- Cabinet door with cylinder lock upon enquiry.

## Design

Order Numbers	Nominal Width	Cabinet		Front Plate	
		Width	Inside Width	Width	Inside Width
1 <b>8569</b> 03	300	385	345	409	341
1 <b>8569</b> 04	400	435	395	459	391
1 <b>8569</b> 05	500	489	449	513	445
1 <b>8569</b> 10	600	574	534	598	530
1 <b>8569</b> 15	750	724	684	748	680
1 <b>8569</b> 20	900	874	834	898	830
1 <b>8569</b> 25	1050	1024	984	1048	980
1 <b>8569</b> 30	1200	1174	1134	1198	1130
1 <b>8569</b> 40	1500	1474	1434	1498	1430

## Order Numbers Dimensions in mm

The holding devices required for the installation of HERZ floor heating and compact distributors or distributors for radiator connection in the distributor cabinet must be ordered separately.

- 1 **8522** 20 Holding device with a distance between bars of 200 mm for distributors 8512, 8513, 8514; 8602, 8603, 8604.
- 1 **8422** 20 Holding device with a distance between bars of 200 mm for distributors 8402, 8403, 8441.

Suitable holding devices are included with HERZ-rod type distributors **8531** and **8532**.

## Holding Devices to be ordered separately

Selection tables for determining the cabinet size overleaf.

## Selection Tables Cabinet Sizes

We reserve the right to make modifications necessitated by technological progress.

Branch-offs (+ single branch-off set)	Distributor length (l max. in mm)			Distributor Cabinet - Order Number 1 <b>8569</b> . .		
	Shutoff valves			Shutoff valves		
	None	Straight Models	Angle Models	None	Straight Models	Angle Models
3 (+1)	219	329	364	03	04 (05)	05
4 (+1)	269	379	414	03	05 (10)	10
5 (+1)	319	429	464	04	10	10 (15)
6 (+1)	369	479	514	05	10 (15)	15
7 (+1)	419	529	564	10	15	15
8 (+1)	469	579	614	10 (15)	15	15 (20)
9 (+1)	519	629	664	15	15 (20)	20
10 (+1)	569	679	714	15	20	20
11 (+1)	619	729	764	15 (20)	20	20 (25)
12 (+1)	669	779	814	20	20 (25)	25
Branch-offs	Distributor length with end cap (l max. in mm)		Distributor Cabinet - Order Number 1 <b>8569</b> . .			
	With shutoff valves		With shutoff valves			
	Straight Models	Angle Models	Straight Models	Angle Models		
3	355	455	04	10		
4	410	510	05	10		
5	465	565	10	15		
6	520	620	10	15		
7	575	675	15	15		
8	630	730	15	20		
9	685	785	20	20		
10	740	840	20	25		
11	795	895	20	25		
12	850	950	25	25		
Branch-offs	Distributor length (l max in mm)		Distributor cabinet Order No. 1 <b>8569</b> . .			
	Transition socket		Transition socket			
	no	yes	no	yes		
3	230	260	03	03		
4	270	300	03	03		
5	310	340	03	04		
6	350	380	04	04		
7	390	420	04	05		
8	430	460	05	10		
9	470	500	10	10		
10	510	540	10	15		
11	550	580	15	15		
12	590	620	15	15		

**Selection table for  
HERZ-rod type  
distributors 8531, 8532**

The order numbers in parentheses are for HERZ-rod type distributors with installed single branch-off sets.

HERZ distributors for up to 16 branch-offs upon enquiry

**Selection table for  
HERZ-floor heating  
distributors 8512, 8513,  
8514, and  
HERZ distributors for  
radiator connection  
(heating circuit  
distributors) 8402, 8403;  
8602, 8603, 8604**

HERZ distributors for up to 16 branch-offs upon enquiry

**Selection table  
for HERZ compact  
distributors 8441**

HERZ distributors for up to 16 branch-offs upon enquiry